

Key Features

Extended Lifespan | Automatic

Sleep Timer | Auto Power Off |

Bright Images in Any Environment |

Amazing Colour Accuracy




AV-Concept ApS Professionelt AV-Udstyr

Product **Description**

The ViewSonic PA503W offers impressive visual performance in small business meeting rooms and classrooms. With higher brightness and longer lamp life, PA503W projector is guaranteed to reproduce the finest of details in any environment for much longer. ViewSonic exclusive SuperColour™ technology offers a wider range of displayable colour ensuring true-to-life colour accuracy in both bright and dark environments without sacrificing image quality.





^{8.} Audio in/out

^{13.} Video

^{14.} Kensington® Lock Slot

Visit Us • www.viewsonic.com

SP

ECIFICATION	OTHERS
-------------	--------

0.65" WXGA 100-240V+/-Projection system: 10%, 50/60Hz Power Supply Voltage:

Native Resolution: 1280x800 AC

DC type: DC3 Normal: 260W Power Consumption: Standby: <0.5W 3600 ANSI Brightness:

Operating Temperature:

Net Weight:

0~40°C

2.2kg

S-Chinese,

Contrast Ratio with SuperEco Carton: Brown 22000:1

Lumens

1.07 Billion Display Colour: Dimensions (WxDxH) Colours 294x218x110mm

w/adjustment foot: Light Source: Lamp

English, French, Light source life (Nor/SuperEco): 5000/15000 Spanish, Thai, Korean, 200W Lamp Watt: German, Italian,

Russian. F=2.56-2.68. Swedish, Dutch, Lens: f=22-24.1 mm Polish, Czech, T-Chinese, Projection Offset: 100%+/-5% Language:

Japanese, Throw Ratio: 1.55~1.70 Turkish, Portuguese, 30" - 300" Image size: Finnish,

1m-10.98m Indonesian, Throw Distance: India, Arabic, (100" @3.34m) Vietnamese

Keystone: ±40° (Vertical) STANDARD ACCESSORY Optical Zoom: 1.1x Power Cord: 1

Audible Noise (Eco): 27dB VGA cable: 1

VGA(640 x 480) Remote Control: 1 **Resolution Support:** to FullHD(1920

x 1080) QSG: 1 / CD: QSG & CD: NA

480i, 480p, 576i, 576p, Air Filter: **RSPL HDTV** Compatibility: 720p, 1080i,

1080p NTSC, PAL, Video Compatibility:

Horizontal Frequency: 15K~102KHz 23~120Hz Vertical Scan Rate:

SECAM

INPUT Computer in (D-SUB 15 pin): 2

Composite: Audio-in (3.5mm):

HDMI: 1 (Back)

OUTPUT

Monitor out (D-SUB 15 pin): 1 Audio out (3.5mm):

Speaker: 2W

USB type mini B (Services):

CONTROL RS232:

AV-Concept ApS Professionelt AV-Udstyr

Copyright © ViewSonic Corporation 2000-2019. All rights reserved. (02/20/2019 07:55:34 America/Chicago)